

## General Purpose ABS SP-9010

SP-9010 is a medium impact rigid ABS sheet, which provides good physical properties at an effective price. Standard stock sheets of 48" x 96" are available in many gauges.

## **General Purpose SP-9010 Data**

| Test                        | Condition     | Units             | Value   |
|-----------------------------|---------------|-------------------|---------|
| Specific Gravity            | ASTM D792     | g/cm <sup>3</sup> | 1.04    |
| Tensile Modulus             | ASTM D638     | psi               | 310,000 |
| Tensile Strength            | ASTM D638     | psi               | 6,000   |
| Flexural Modulus            | ASTM D790     | psi               | 340,000 |
| Flexural Strength           | ASTM D790     | psi               | 10,000  |
| Izod Impact                 | ASTM D256     | Ft-lbs/in.        | 7.5     |
|                             | (73°F, -40°C) |                   | 2.5     |
| Falling Dart Impact         | ASTM D3029    | Ft-lbs            | 33      |
|                             | (73°F, -40°C) |                   | 12      |
| Heat Deflection Temperature | ASTM D648     | °F                | 198     |
| Hardness                    | ASTM D785     | Rockwell R        | 105     |
| Gardner Gloss               | ASTM D523     | %                 | 90      |
| Flammability Rating         | MVSS 302      |                   | Passes  |
|                             | UL94 HB       |                   | Passes  |

IMPORTANT: The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Lehigh Valley Plastics, Inc. will not be held responsible for the use of this information relative to actual application.